



OVERALL WIDTH: 4.750"
1/2 OF FACE: 1.625"
L MEASUREMENT: 1.750"
WEB-TO-HUB EXTENSION R: 2.023"
FACE-TO-HUB EXTENSION L: 1.250"
FACE-TO-HUB EXTENSION R: 1.500"
APPROXIMATE WEIGHT (LBS.): 15

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE DIAMETER: +0.000"/-0.001"

APPROVED BY: _____ **SIGNATURE:** _____ **DATE:** _____

D	F	O	H	B		S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
6.000"	3.250"	3.125"	3.500"	0.375"	0.000"	0.000"	0.000"

UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES
DIMENSIONS: ± 0.010 "
FINISH: 250  EXCEPT FOR BORE AND OUTER
FACE WHICH SHOULD BE 63 

BRAKE PRODUCTS, INC.
16751 HILLTOP PARK PLACE
CHAGRIN FALLS, OH 44023
UNITED STATES OF AMERICA
Web: www.brakeproducts.com
Email: sales@brakeproducts.com
Phone: (440) 543-7962
Fax: (440) 543-7963

FOR TM-63 AND OTHER 6 INCH BRAKES

DATE: Sunday, Feb 7 2016 **PART #** BE061001 **MATERIAL SPECIFICATION:** DUCTILE IRON ASTM A536-84 80-55-06

DESCRIPTION: 6 INCH BORED & KEYED BRAKE WHEEL **SERIAL #** 16