



OVERALL WIDTH: 5.625"
1/2 OF FACE: 1.625"
L MEASUREMENT: 2.000"
WEB-TO-HUB EXTENSION R: 1.479"
FACE-TO-HUB EXTENSION L: 2.625"
FACE-TO-HUB EXTENSION R: 2.375"
APPROXIMATE WEIGHT (LBS.): 18
SMALL BORE DIAMETER: 1.438"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B	B	S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
8.000"	3.250"	4.000"	3.000"	1.750"	1.250"	0.500"	0.250"
<p>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</p> <p>DIMENSIONS: ± 0.010"</p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p>				<p>BRAKE PRODUCTS, INC. 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p>		<p>Web: www.brakeproducts.com Email: sales@brakeproducts.com Phone: (440) 543-7962 Fax: (440) 543-7963</p>	
<p>DATE: Saturday, Oct 28 2017</p>				<p>PART # BE081013</p>		<p>MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06</p>	
<p>DESCRIPTION: 8 INCH BORED & KEYED BRAKE WHEEL</p>						<p>SERIAL # 0</p>	

HUB LENGTH BORE & KEYWAY FOR A 602, 802, AC1, AC2, AC4, MCS2, MD402AE, SW5 MTRS
AISE STANDARD OFFSET IS 4 INCHES
24 LBS SMX-802/W SUPERNUT GH505JXA01 E008514