



OVERALL WIDTH: 7.875"
1/2 OF FACE: 2.875"
L MEASUREMENT: 3.125"
WEB-TO-HUB EXTENSION R: 1.856"
FACE-TO-HUB EXTENSION L: 3.875"
FACE-TO-HUB EXTENSION R: 2.125"
APPROXIMATE WEIGHT (LBS.): 66
SMALL BORE DIAMETER: 2.083"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B		S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
13.000"	5.750"	5.000"	4.000"	2.500"	1.250"	0.500"	0.250"
<p><u>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</u></p> <p>DIMENSIONS: ± 0.010"</p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p>				<p>BRAKE PRODUCTS, INC. 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p>		<p>Web: www.brakeproducts.com Email: sales@brakeproducts.com Phone: (440) 543-7962 Fax: (440) 543-7963</p>	
<p>DATE: Saturday, Oct 28 2017</p>				<p>HUB LENGTH BORE AND KEYWAY FOR A 606 806 ACE MOTOR AISE STANDARD OFFSET OF 5 INCHES 118B8885P3 GH505LXC02 E013544 407043 13F1701D1</p>		<p>PART # BE131003</p>	
<p>DESCRIPTION: 13 INCH BORED & KEYED BRAKE WHEEL</p>				<p>MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06</p>		<p>SERIAL # 0</p>	