



OVERALL WIDTH: 8.250"
1/2 OF FACE: 2.875"
L MEASUREMENT: 3.500"
WEB-TO-HUB EXTENSION R: 2.270"
FACE-TO-HUB EXTENSION L: 3.750"
FACE-TO-HUB EXTENSION R: 2.500"
APPROXIMATE WEIGHT (LBS.): 63
SMALL BORE DIAMETER: 2.531"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B	BORE TAPER IN/FT	S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
13.000"	5.750"	5.375"	4.500"	3.000"	1.250"	0.750"	0.250"
<p>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</p> <p>DIMENSIONS: ± 0.010"</p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p>				<p>BRAKE PRODUCTS, INC. 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p>		<p>Web: www.brakeproducts.com Email: sales@brakeproducts.com Phone: (440) 543-7962 Fax: (440) 543-7963</p>	
<p>DATE: Saturday, Oct 28 2017</p>				<p>HUB LENGTH BORE & KEYWAY FOR A 608 & 808 MILL MOTOR AISE STANDARD OFFSET OF 5.375 INCHES 118B8885P1 E013513 GH505-LX- C03 SMX-808/W</p>		<p>PART # BE131004</p>	
<p>DESCRIPTION: 13 INCH BORED & KEYED BRAKE WHEEL</p>						<p>MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06</p>	
						<p>SERIAL # 0</p>	