

TOLERANCES: WHEEL DIAMETER: +0.005"/-0.000" BORE TAPER: +0.000"/-0.003"

SERIAL# 0

APPROVED BY:			SIGNATURE:			DATE:		
D	F	0	Н		В		S	Т
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH		BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
13.000"	5.750"	5.000"	3.875"		2.375"	1.250"	0.625"	0.313"
UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES DIMENSIONS: ±0.010" FINISH: 250 EXCEPT FOR BORE AND OUTER FACE WHICH SHOULD BE 63				BRAKE PRODUCTS, INC. 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA HUB LENGTH BORE & KEYWAY FOR THE FOLLOWING MOTORS 404X 405 407 409 444TZ L407 L409 118B8902P30 409AT Web: www.brakeproducts.com Email: sales@brakeproducts.com Email: sales@brakeprod			akeproducts.com 3-7962	
DATE: Saturday, Oct 28 2017				PAR	PARITE BETATOTA		MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06	

CL

DESCRIPTION: 13 INCH BORED & KEYED BRAKE WHEEL