



TOLERANCES: WHEEL DIAMETER: +0.005"/-0.000" BORE TAPER: +0.000"/-0.003"

APPROVED E	SIGNATURE:			DATE:				
D	F	0	Н		В		S	Т
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH		BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
16.000"	6.750"	6.500"	5.000"		3.625"	1.250"	0.750"	0.250"
UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES DIMENSIONS: ±0.010" FINISH: 250 EXCEPT FOR BORE AND OUTER FACE WHICH SHOULD BE 63					BRAKE PRODUCTS, INC. 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA BORED & KEYED FOR A 612 / 812 MILL MOTOR WITH AN AISE STANDARD OFFSET 118B8887P6 AC30 E016506 GH505-MX-D04 Web: www.brakeproducts.com Email: sales@brakeproducts.com Phone: (440) 543-7962 Fax: (440) 543-7963			
DATE: Saturday, Oct 28 2017			PAR	PARI # BE16100/		MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06		
DESCRIPTION: 16 INCH BORED & KEYED BRAKE WHEEL							SERIAL# 0	