



OVERALL WIDTH: 11.875"
1/2 OF FACE: 4.375"
L MEASUREMENT: 3.700"
WEB-TO-HUB EXTENSION R: 2.059"
FACE-TO-HUB EXTENSION L: 7.375"
FACE-TO-HUB EXTENSION R: 3.125"
APPROXIMATE WEIGHT (LBS.): 190
SMALL BORE DIAMETER: 2.781"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B		S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
19.000"	8.750"	7.500"	4.500"	3.250"	1.250"	0.750"	0.250"

UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES

DIMENSIONS: ± 0.010 "
FINISH: 250  EXCEPT FOR BORE AND OUTER

FACE WHICH SHOULD BE 63 

BRAKE PRODUCTS, INC.
16751 HILLTOP PARK PLACE
CHAGRIN FALLS, OH 44023
UNITED STATES OF AMERICA

Web: www.brakeproducts.com
Email: sales@brakeproducts.com
Phone: (440) 543-7962
Fax: (440) 543-7963

HUB LENGTH BORE & KEYWAY FOR A 610 / 810 MILL MOTOR 3.245 / 3.25
AISE STANDARD OFFSET OF 7.5 INCHES 1/32 BCR ON KEYWAY
#2 BOF MRG 7346 CRANE 11A AUX HOIST ITEM 5 DRAWING 309708

DATE: Saturday, Dec 2 2017

PART # BE191007

MATERIAL SPECIFICATION:
DUCTILE IRON ASTM A536-84 80-55-06

DESCRIPTION: 19 INCH BORED & KEYED BRAKE WHEEL

SERIAL # 0