

FACE-TO-HUB EXTENSION R: 2.625"
APPROXIMATE WEIGHT (LBS.): 375
SMALL BORE DIAMETER: 3.729"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"

BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	0	Н	В		S	Т
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
23.000"	11.250"	8.250"	5.000"	4.250"	1.250"	1.000"	0.375"

CL

BRAKE PRODUCTS, INC. Web: www.brakeproducts.com UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES 16751 HILLTOP PARK PLACE Email: sales@brakeproducts.com CHAGRIN FALLS, OH 44023 DIMENSIONS: ±0.010" Phone: (440) 543-7962 250 FINISH: EXCEPT FOR BORE AND OUTER UNITED STATES OF AMERICA Fax: (440) 543-7963 FACE WHICH SHOULD BE 63 HUB LENGTH BORE & KEYWAY FOR A 614 MILL MOTOR WITH THE AISE OFFSET OF 8.25 INCH 11901T197 1992-CM-08 1258680 NUCR DRW 395676 M/S FURNACE MS DETAIL 1/16 INCH BCR MATERIAL SPECIFICATION: PART # BE231004 DATE: Saturday, Oct 28 2017 DUCTILE IRON ASTM A536-84 80-55-06 SERIAL# 0 **DESCRIPTION: 23 INCH BORED & KEYED BRAKE WHEEL**