



OVERALL WIDTH: 15.375"
 1/2 OF FACE: 5.625"
 L MEASUREMENT: 5.525"
 WEB-TO-HUB EXTENSION R: 2.944"
 FACE-TO-HUB EXTENSION L: 6.125"
 FACE-TO-HUB EXTENSION R: 4.125"
 APPROXIMATE WEIGHT (LBS.): 213
 SMALL BORE DIAMETER: 6.036"

TOLERANCES:
 WHEEL DIAMETER: +0.005"/-0.000"
 BORE TAPER: +0.000"/-0.003"

APPROVED BY: _____ **SIGNATURE:** _____ **DATE:** _____

D	F	O	H	B	B	S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
23.000"	11.250"	9.750"	9.250"	7.000"	1.250"	1.500"	0.750"

UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES
 DIMENSIONS: ±0.010"
 FINISH: 250 EXCEPT FOR BORE AND OUTER
 FACE WHICH SHOULD BE 63

BRAKE PRODUCTS, INC.
 16751 HILLTOP PARK PLACE
 CHAGRIN FALLS, OH 44023
 UNITED STATES OF AMERICA
 Web: www.brakeproducts.com
 Email: sales@brakeproducts.com
 Phone: (440) 543-7962
 Fax: (440) 543-7963

118B889P14
 HUB LENGTH BORE & KEYWAY FOR A 624 MILL MOTOR
 302817

DATE: Saturday, Oct 28 2017 **PART #** BE231008 **MATERIAL SPECIFICATION:** DUCTILE IRON ASTM A536-84 80-55-06

DESCRIPTION: 23 INCH BORED & KEYED BRAKE WHEEL **SERIAL #** 0