



OVERALL WIDTH: 5.625"
1/2 OF FACE: 1.625"
L MEASUREMENT: 1.875"
WEB-TO-HUB EXTENSION R: 2.301"
FACE-TO-HUB EXTENSION L: 1.625"
FACE-TO-HUB EXTENSION R: 2.375"
APPROXIMATE WEIGHT (LBS.): 13
SMALL BORE DIAMETER: 2.083"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B		S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
8.000"	3.250"	4.000"	4.000"	2.500"	1.250"	0.500"	0.250"

UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES

DIMENSIONS: $\pm 0.010"$
FINISH: 250 ∇ EXCEPT FOR BORE AND OUTER
FACE WHICH SHOULD BE 63 ∇

BRAKE PRODUCTS, INC.
16751 HILLTOP PARK PLACE
CHAGRIN FALLS, OH 44023
UNITED STATES OF AMERICA

Web: www.brakeproducts.com
Email: sales@brakeproducts.com
Phone: (440) 543-7962
Fax: (440) 543-7963

HUB LENGTH BORE & KEYWAY FO 606 806 AC8 MOTORS
118B8881P6 GH505JXA03
SMX-806/W SUPERNUT

DATE: Saturday, Oct 28 2017	PART # BE081016	MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06
DESCRIPTION: 8 INCH BORED & KEYED BRAKE WHEEL		SERIAL # 0