



OVERALL WIDTH: 4.875"
1/2 OF FACE: 1.625"
L MEASUREMENT: 1.875"
WEB-TO-HUB EXTENSION R: 2.158"
FACE-TO-HUB EXTENSION L: 1.875"
FACE-TO-HUB EXTENSION R: 1.625"
APPROXIMATE WEIGHT (LBS.): 18
SMALL BORE DIAMETER: 1.313"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B	B	S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
8.000"	3.250"	3.250"	3.000"	1.625"	1.250"	0.375"	0.188"
<p><u>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</u></p> <p>DIMENSIONS: ± 0.010"</p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p>				<p>BRAKE PRODUCTS, INC. 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p> <p>Web: www.brakeproducts.com Email: sales@brakeproducts.com Phone: (440) 543-7962 Fax: (440) 543-7963</p>			<p>QUOTE RANDY @ KONECRANES QTY 1 07/22/13 SPECIAL METALS FA9332 CRANE 1259 BRIDGE BRAKE WHEEL DRAWING A-1259-B15 BORE TOLERANCE 1.625/ 1.624 LOCKWASHER SLOT 0.125 WIDE 0.6875 DEEP 2.25 LONG 0.2187 FROM CTR TO EDGE</p>
DATE: Monday, Jul 22 2013				PART # BE089118		MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06	
DESCRIPTION: 8 INCH BORED & KEYED BRAKE WHEEL						SERIAL # 88	

