



OVERALL WIDTH: 5.375"  
1/2 OF FACE: 1.625"  
L MEASUREMENT: 1.625"  
WEB-TO-HUB EXTENSION R: 1.512"  
FACE-TO-HUB EXTENSION L: 2.625"  
FACE-TO-HUB EXTENSION R: 2.125"  
APPROXIMATE WEIGHT (LBS.): 16

TOLERANCES:  
WHEEL DIAMETER: +0.005"/-0.000"  
BORE DIAMETER: +0.000"/-0.001"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B		S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
8.000"	3.250"	3.750"	2.750"	1.623"	0.000"	0.375"	0.188"
<p>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</p> <p>DIMENSIONS: <math>\pm 0.010</math>"</p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p>				<p><b>BRAKE PRODUCTS, INC.</b> 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p>		<p>Web: <a href="http://www.brakeproducts.com">www.brakeproducts.com</a> Email: <a href="mailto:sales@brakeproducts.com">sales@brakeproducts.com</a> Phone: (440) 543-7962 Fax: (440) 543-7963</p>	
<p>DATE: Saturday, Oct 28 2017</p>				<p>BORE TOLERANCE 1.6230 / 1.6220 171B3268P2 277A8137</p>			
<p>DESCRIPTION: 8 INCH BORED &amp; KEYED BRAKE WHEEL</p>				<p>PART # BE081010</p>		<p>MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06</p>	
						<p>SERIAL # 0</p>	