



OVERALL WIDTH: 17.875"
1/2 OF FACE: 7.125"
L MEASUREMENT: 7.250"
WEB-TO-HUB EXTENSION R: 3.947"
FACE-TO-HUB EXTENSION L: 10.625"
FACE-TO-HUB EXTENSION R: 3.625"
APPROXIMATE WEIGHT (LBS.): 630
SMALL BORE DIAMETER: 5.495"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

APPROVED BY: _____ **SIGNATURE:** _____ **DATE:** _____

D	F	O	H	B	B	S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
30.000"	14.250"	10.750"	7.250"	6.250"	1.250"	1.500"	0.750"

UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES

DIMENSIONS: ± 0.010 "
FINISH: 250  EXCEPT FOR BORE AND OUTER

FACE WHICH SHOULD BE 63 

BRAKE PRODUCTS, INC.
16751 HILLTOP PARK PLACE
CHAGRIN FALLS, OH 44023
UNITED STATES OF AMERICA

Web: www.brakeproducts.com
Email: sales@brakeproducts.com
Phone: (440) 543-7962
Fax: (440) 543-7963

HUB LENGTH BORE AND KEYWAY FOR A 622 MILL MOTOR 1258685
10.75 INCHES IS THE AISE STANDARD FOR THIS MILL MOTOR
QTY. 4, 3 INCH DIA PULLING / LIFTING HOLES SPACED AT 90 DEGREES

DATE: Thursday, Oct 26 2017

PART # BE301005

MATERIAL SPECIFICATION:
DUCTILE IRON ASTM A536-84 80-55-06

DESCRIPTION: 30 INCH BORED & KEYED BRAKE WHEEL

SERIAL # 0