



OVERALL WIDTH: 6.125"
1/2 OF FACE: 1.875"
L MEASUREMENT: 2.250"
WEB-TO-HUB EXTENSION R: 1.665"
FACE-TO-HUB EXTENSION L: 2.625"
FACE-TO-HUB EXTENSION R: 2.375"
APPROXIMATE WEIGHT (LBS.): 29
SMALL BORE DIAMETER: 1.635"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B		S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
10.000"	3.750"	4.250"	3.500"	2.000"	1.250"	0.500"	0.250"
<p>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</p> <p>DIMENSIONS: ± 0.010"</p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p>				<p>BRAKE PRODUCTS, INC. 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p>		<p>Web: www.brakeproducts.com Email: sales@brakeproducts.com Phone: (440) 543-7962 Fax: (440) 543-7963</p>	
<p>DATE: Saturday, Oct 28 2017</p>				<p>PART # BE101014</p>		<p>MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06</p>	
<p>DESCRIPTION: 10 INCH BORED & KEYED BRAKE WHEEL</p>						<p>SERIAL # 0</p>	

HUB LENGTH BORE & KEYWAY FOR A 403, 404, 603, 604, 803, 604, 804 MCS4, MD404AE
THE AISE STANDARD OFFSET 4.25 INCHES 118B8883P6 GH505KXB02 E010503
13F1518D1 GE 85164-2 FOR A GE A-101 51002-041-02 9506059 EM204751