



OVERALL WIDTH: 6.125"
1/2 OF FACE: 1.875"
L MEASUREMENT: 2.250"
WEB-TO-HUB EXTENSION R: 1.793"
FACE-TO-HUB EXTENSION L: 2.125"
FACE-TO-HUB EXTENSION R: 2.375"
APPROXIMATE WEIGHT (LBS.): 27
SMALL BORE DIAMETER: 2.083"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

| APPROVED BY: | | | SIGNATURE: | | | DATE: | |
|--|------------|------------|------------|--|------------------|--|--------------|
| D | F | O | H | B | | S | T |
| WHEEL DIAMETER | FACE WIDTH | HUB OFFSET | HUB LENGTH | BORE DIAMETER | BORE TAPER IN/FT | KEYWAY WIDTH | KEYWAY DEPTH |
| 10.000" | 3.750" | 4.250" | 4.000" | 2.500" | 1.250" | 0.500" | 0.250" |
| <p><u>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</u></p> <p>DIMENSIONS: ±0.010"</p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p> | | | | <p>BRAKE PRODUCTS, INC. 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p> | | <p>Web: www.brakeproducts.com Email: sales@brakeproducts.com Phone: (440) 543-7962 Fax: (440) 543-7963</p> | |
| <p>DATE: Saturday, Oct 28 2017</p> | | | | <p>PART # BE101015</p> | | <p>MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06</p> | |
| <p>DESCRIPTION: 10 INCH BORED & KEYED BRAKE WHEEL</p> | | | | | | <p>SERIAL # 0</p> | |

HUB LENGTH BORE & KEYWAY FOR 606, 806, AC8, & AC12 MOTORS
118B8883P7 GH505KXB03 E010535 13F1973
ALLIA B10BW02 140A1581 B10BW02 38 LBS