



OVERALL WIDTH: 7.875"  
1/2 OF FACE: 2.875"  
L MEASUREMENT: 3.000"  
WEB-TO-HUB EXTENSION R: 1.738"  
FACE-TO-HUB EXTENSION L: 4.375"  
FACE-TO-HUB EXTENSION R: 2.125"  
APPROXIMATE WEIGHT (LBS.): 68  
SMALL BORE DIAMETER: 1.635"

TOLERANCES:  
WHEEL DIAMETER: +0.005"/-0.000"  
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B		S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
13.000"	5.750"	5.000"	3.500"	2.000"	1.250"	0.500"	0.250"
<p><u>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</u></p> <p>DIMENSIONS: <math>\pm 0.010</math>"</p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p>				<p><b>BRAKE PRODUCTS, INC.</b> 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p>		<p>Web: <a href="http://www.brakeproducts.com">www.brakeproducts.com</a> Email: <a href="mailto:sales@brakeproducts.com">sales@brakeproducts.com</a> Phone: (440) 543-7962 Fax: (440) 543-7963</p>	
<p>DATE: Saturday, Oct 28 2017</p>				<p>HUB LENGTH, OFFSET, BORE &amp; KEYWAY FOR A 403 404 603 604 803 804 MCS4 MD404AE2 MD604 SW10 ALLI DRW 689OT89 118B8926P12 GH505LXC01 E013543</p>		<p><b>MATERIAL SPECIFICATION:</b> DUCTILE IRON ASTM A536-84 80-55-06</p>	
<p>DESCRIPTION: 13 INCH BORED &amp; KEYED BRAKE WHEEL</p>						<p>PART # BE131002</p> <p>SERIAL # 0</p>	