



OVERALL WIDTH: 9.875"  
1/2 OF FACE: 3.375"  
L MEASUREMENT: 3.625"  
WEB-TO-HUB EXTENSION R: 2.100"  
FACE-TO-HUB EXTENSION L: 4.875"  
FACE-TO-HUB EXTENSION R: 3.125"  
APPROXIMATE WEIGHT (LBS.): 94  
SMALL BORE DIAMETER: 3.729"

TOLERANCES:  
WHEEL DIAMETER: +0.005"/-0.000"  
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B	BORE TAPER IN/FT	S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
16.000"	6.750"	6.500"	5.000"	4.250"	1.250"	1.000"	0.375"
<p>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</p> <p>DIMENSIONS: <math>\pm 0.010"</math></p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p>				<p><b>BRAKE PRODUCTS, INC.</b> 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p>		<p>Web: <a href="http://www.brakeproducts.com">www.brakeproducts.com</a> Email: <a href="mailto:sales@brakeproducts.com">sales@brakeproducts.com</a> Phone: (440) 543-7962 Fax: (440) 543-7963</p>	
<p>DATE: Saturday, Oct 28 2017</p>				<p>HUB LENGTH BORE &amp; KEYWAY FOR A 614 MILL MOTOR WITH THE AISE STANDARD OFFSET DWG 164485 AISE STANDARD OFFSET 6.5 INCHES</p>		<p><b>PART #</b> BE161005</p>	
<p><b>DESCRIPTION:</b> 16 INCH BORED &amp; KEYED BRAKE WHEEL</p>				<p><b>MATERIAL SPECIFICATION:</b> DUCTILE IRON ASTM A536-84 80-55-06</p>		<p><b>SERIAL #</b> 0</p>	