



OVERALL WIDTH: 9.875"
1/2 OF FACE: 3.375"
L MEASUREMENT: 3.750"
WEB-TO-HUB EXTENSION R: 2.225"
FACE-TO-HUB EXTENSION L: 5.375"
FACE-TO-HUB EXTENSION R: 3.125"
APPROXIMATE WEIGHT (LBS.): 118

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE DIAMETER: +0.000"/-0.001"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B		S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
16.000"	6.750"	6.500"	4.500"	2.873"	0.000"	0.750"	0.375"
<p>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</p> <p>DIMENSIONS: ± 0.010"</p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p>				<p>BRAKE PRODUCTS, INC. 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p>		<p>Web: www.brakeproducts.com Email: sales@brakeproducts.com Phone: (440) 543-7962 Fax: (440) 543-7963</p>	
<p>DATE: Saturday, Oct 28 2017</p>				<p>PART # BE161012</p>		<p>MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06</p>	
<p>DESCRIPTION: 16 INCH BORED & KEYED BRAKE WHEEL</p>						<p>SERIAL # 0</p>	

BORE TOLERANCE 2.8730 / 2.8720
277A8190P15 139B7155P34 305A1265P15 277A8151
CD 504AT, L504AT, 506AT, L506AT, 508AT, L508AT