



OVERALL WIDTH: 11.875"
1/2 OF FACE: 4.375"
L MEASUREMENT: 3.400"
WEB-TO-HUB EXTENSION R: 2.184"
FACE-TO-HUB EXTENSION L: 6.875"
FACE-TO-HUB EXTENSION R: 3.125"
APPROXIMATE WEIGHT (LBS.): 197
SMALL BORE DIAMETER: 3.104"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B		S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
19.000"	8.750"	7.500"	5.000"	3.625"	1.250"	0.750"	0.250"
<p>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</p> <p>DIMENSIONS: ± 0.010"</p> <p>FINISH: 250  EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 </p>				<p>BRAKE PRODUCTS, INC. 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p>		<p>Web: www.brakeproducts.com Email: sales@brakeproducts.com Phone: (440) 543-7962 Fax: (440) 543-7963</p>	
<p>DATE: Tuesday, May 23 2017</p>				<p>PART # BE191003</p>		<p>MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06</p>	
<p>DESCRIPTION: 19 INCH BORED & KEYED BRAKE WHEEL</p>						<p>SERIAL # 0</p>	

BRAKE PRODUCTS, INC.
16751 HILLTOP PARK PLACE
CHAGRIN FALLS, OH 44023
UNITED STATES OF AMERICA

Web: www.brakeproducts.com
Email: sales@brakeproducts.com
Phone: (440) 543-7962
Fax: (440) 543-7963

HUB LENGTH BORE & KEYWAY FOR 412, 612, 812, AC25, AC30, MCS12, MD412AE, MD412AE2
AISE STANDARD OFFSET OF 7.5 INCHES
118B8889P5 GH505NXE03 2219AG 20747-500