



OVERALL WIDTH: 7.500"
1/2 OF FACE: 3.250"
L MEASUREMENT: 3.000"
WEB-TO-HUB EXTENSION R: 2.625"
FACE-TO-HUB EXTENSION L: 3.500"
FACE-TO-HUB EXTENSION R: 1.000"
APPROXIMATE WEIGHT (LBS.): 88
SMALL BORE DIAMETER: 2.083"

TOLERANCES:
WHEEL DIAMETER: +0.005"/-0.000"
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B		S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
14.000"	6.500"	4.250"	4.000"	2.500"	1.250"	0.500"	0.250"
<p>UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES</p> <p>DIMENSIONS: $\pm 0.010"$</p> <p>FINISH: 250 ∇ EXCEPT FOR BORE AND OUTER</p> <p>FACE WHICH SHOULD BE 63 ∇</p>				<p>BRAKE PRODUCTS, INC. 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA</p>		<p>Web: www.brakeproducts.com Email: sales@brakeproducts.com Phone: (440) 543-7962 Fax: (440) 543-7963</p>	
<p>DATE: Sunday, Nov 19 2017</p>				<p>HUB LENGTH, BORE & KEYWAY FOR A 606 806 AC8 AC12 MOTORS ALLIDRW6360B27 JE76278 SUP-SMX-806/W SUPERNUT</p>		<p>PART # BH141007</p>	
<p>DESCRIPTION: 14 INCH BORED & KEYED BRAKE WHEEL</p>				<p>MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06</p>		<p>SERIAL # 0</p>	