



OVERALL WIDTH: 7.500"  
1/2 OF FACE: 3.250"  
L MEASUREMENT: 3.000"  
WEB-TO-HUB EXTENSION R: 2.625"  
FACE-TO-HUB EXTENSION L: 3.000"  
FACE-TO-HUB EXTENSION R: 1.000"  
APPROXIMATE WEIGHT (LBS.): 76  
SMALL BORE DIAMETER: 2.781"

TOLERANCES:  
WHEEL DIAMETER: +0.005"/-0.000"  
BORE TAPER: +0.000"/-0.003"

APPROVED BY:			SIGNATURE:			DATE:	
D	F	O	H	B		S	T
WHEEL DIAMETER	FACE WIDTH	HUB OFFSET	HUB LENGTH	BORE DIAMETER	BORE TAPER IN/FT	KEYWAY WIDTH	KEYWAY DEPTH
14.000"	6.500"	4.250"	4.500"	3.250"	1.250"	0.750"	0.250"
UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES DIMENSIONS: $\pm 0.010$ " FINISH: 250  EXCEPT FOR BORE AND OUTER FACE WHICH SHOULD BE 63 				<b>BRAKE PRODUCTS, INC.</b> 16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA		Web: <a href="http://www.brakeproducts.com">www.brakeproducts.com</a> Email: <a href="mailto:sales@brakeproducts.com">sales@brakeproducts.com</a> Phone: (440) 543-7962 Fax: (440) 543-7963	
DATE: Sunday, Nov 19 2017				PART # BH141008		MATERIAL SPECIFICATION: DUCTILE IRON ASTM A536-84 80-55-06	
DESCRIPTION: 14 INCH BORED & KEYED BRAKE WHEEL						SERIAL # 0	

HUB LENGTH BORE & KEYWAY FOR 410 610 810 AC18 MC10 MD410AE2 MS10 MOTORS  
JE76279 TID 9506085