

| D   | F               | 0          | H          |                      | В  |                  | S                                      | T            |
|---|-----------------|------------|------------|----------------------|--|------------------|--|--------------|
| WHEEL DIAMETER  | FACE WIDTH      | HUB OFFSET | HUB LENGTH |                      | BORE DIAMETER  | BORE TAPER IN/FT | KEYWAY WIDTH                           | KEYWAY DEPTH |
| 18.000"   | 8.500"          | 5.250"     | 4.500"     |                      | 3.250"   | 1.250"           | 0.750"                                 | 0.250"       |
| UNLESS OTHERWISE SPECIFIED DRAWING TOLERANCES  DIMENSIONS: ±0.010" FINISH: 250 EXCEPT FOR BORE AND OUTER  FACE WHICH SHOULD BE 63 |                 |            |            | 1675<br>CHAO<br>UNIT | BRAKE PRODUCTS, INC.  16751 HILLTOP PARK PLACE CHAGRIN FALLS, OH 44023 UNITED STATES OF AMERICA  HUB LENGTH BORE & KEYWAY FOR A 610 MILL MOTOR JE76322 410 610 810 AC18 MC10 MD410AE2 MS10  Web: www.brakeproducts.com Email: sales@brakeproducts.com (440) 543-7962 Fax: (440) 543-7963 |                  |  |              |
| DATE: Sunda   | ay, Oct 29 2017 |            |            | PAR                  | <b>T#</b> BH181007   |                  | MATERIAL SPECIFIC<br>DUCTILE IRON ASTM |              |
| <b>DESCRIPTION:</b> 18 INCH BORED & KEYED BRAKE WHEEL   |                 |            |            |                      |  |                  | SERIAL# 0                              |              |